

SAFETY DATA SHEET

27.967: Pelikan black / cyan / magenta / yellow toner for HP LaserJet CP1215 / 1515n

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME 27.967: Pelikan black / cyan / magenta / yellow toner for HP LaserJet CP1215 / 1515n

SUPPLIER Pelikan Hardcopy European

Logistics & Services GmbH Neue Strasse 19

D-52382 Niederzier 2

Germany

+49 (0) 2428 830

olaf.lehmann@phiag.com

EMERGENCY TELEPHONE +41 (0) 44 986 1111 (available only during office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BLUE COLOURANT	235-546-0	12270-13-2	1-5%	-
BLUE COLOURANT		4444-01-3	1-5%	-
CHARGE CONTROL AGENT (confidential CAS Number)			1-5%	-
MAGENTA COLOURANT	255-785-4	42373-04-6	1-5%	-
PARAFFIN WAX	232-315-6	8002-74-2	1-5%	-
POLYESTER RESIN (confidential CAS Number)			60-100%	-
RED COLOURANT	237-946-0	14097-03-1	1-5%	-
SILICA - ALKYLATED	272-697-1	68909-20-6	1-5%	-
YELLOW COLOURANT	281-435-5	83949-75-1	1-5%	-

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

When in doubt or symptoms persist, seek medical attention.

INHALATION

General first aid, rest, warmth and fresh air.

INGESTION

Immediately rinse mouth and drink plenty of water (200-300 ml).

SKIN CONTACT

Wash skin thoroughly with soap and water.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Carbon dioxide (CO2). Water spray, fog or mist. Foam. Dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

REVISION DATE: A / 13.05.09

27.967: Pelikan black / cyan / magenta / yellow toner for HP LaserJet CP1215 / 1515n

SPECIFIC HAZARDS

Dust may form an explosive mixture in the atmosphere. In case of fire, toxic gases may be formed.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Use protective gloves, goggles and suitable protective clothing. Do not smoke, use naked flames or other sources of ignition.

SPILL CLEAN UP METHODS

Avoid generation and spreading of dust. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into closed container. Wash contaminated area with water. For waste disposal, see section 13.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Observe good industrial hygiene practices. Keep away from heat, sparks and open flame. Do not eat, drink or smoke when using the product. Avoid handling which leads to dust formation. Avoid inhalation of dust and contact with skin and eyes.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Store away from Oxidising material - Keep away from flammable and combustible materials. Keep away from food, drink and animal feeding stuffs. Keep out of the reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

STD

General dust recommended limits (UK): 10 mg/m3 (8-hour TWA) total inhalable dust or 4 mg/m3 (8-hour TWA) total respirable dust.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

HAND PROTECTION

Protective gloves are recommended.

EYE PROTECTION

Wear dust resistant safety goggles where there is danger of eye contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Powder, dust

COLOUR Black Blue Red Yellow

ODOUR Slight odour

SOLUBILITY Insoluble in water

BOILING POINT (°C) NA > 60 MELTING POINT (°C) **BULK DENSITY** ND **VAPOUR PRESSURE** NA **EVAPORATION RATE** NA pH-VALUE, DILUTED SOLUTION NA FLASH POINT (°C) ND **AUTO IGNITION** ND

TEMPERATURE (°C)

FLAMMABILITY LIMIT - LOWER(%) ND FLAMMABILITY LIMIT - UPPER(%) ND

PARTITION COEFFICIENT NA

(N-Octanol/Water)

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Decomposition products may include toxic phenols.

11 TOXICOLOGICAL INFORMATION

REVISION DATE: A / 13.05.09

27.967: Pelikan black / cyan / magenta / yellow toner for HP LaserJet CP1215 / 1515n

INHALATION

Dust may irritate respiratory system or lungs.

INGESTION

No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Powder may irritate skin.

EYE CONTACT

May cause temporary eye irritation.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product is not expected to be hazardous to the environment. Volatile organic compounds (VOC): 0%.

WATER HAZARD CLASSIFICATION

N/A

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal should be in accordance with local, state or national legislation.

DISPOSAL METHODS

Powder to be collected, sealed tightly in bags and disposed on approved landfills.

WASTE CLASS

List of Wastes (ref: Decision 2000/532/EC): 08 03 18.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified

SAFETY PHRASES

NC Not classified.

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974.

ENVIRONMENTAL LISTING

Environmental Protection Act 1990. Pollution Prevention and Control Act 1999.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

 $Chemicals \ (Hazard\ Information\ and\ Packaging)\ Regulations.\ Control\ of\ Substances\ Hazardous\ to\ Health.$

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits EH40. Hazardous Waste Regulations 2005. List of Wastes Regulations 2005. The Solvent Emissions Regulations 2004.

16 OTHER INFORMATION

REVISION DATE: A / 13.05.09

27.967: Pelikan black / cyan / magenta / yellow toner for HP LaserJet CP1215 / 1515n

GENERAL INFORMATION

NA = not applicable. NC = not classified. ND = no data. TWA = time-weighted average. Not classified as hazardous for users. This Safety Data Sheet satisfies the requirements of the REACH Regulation (EC): No 1907/2006, as corrected. Article 31. All brand names and trademarks are the property of their respective holders and are used here for descriptive purposes only.

REVISION COMMENTS

This is first issue.

REVISION DATE A / 13.05.09

SDS NO. 27.967

RISK PHRASES IN FULL

NC Not classified.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.