



## SAFETY DATA SHEET

### 27.189: Pelikan toner for Oki B410 / B430 / B440 / B4100 / B4200 / B4300 / B2200 / B2400 / B4400 / B4600

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	27.189: Pelikan toner for Oki B410 / B430 / B440 / B4100 / B4200 / B4300 / B2200 / B2400 / B4400 / B4600		
SUPPLIER	Pelikan Hardcopy European Logistics & Services GmbH Neue Strasse 19 D-52382 Niederzier 2 Germany +49 (0) 2428 830 Olaf Lehmann olaf.lehmann@phpag.com	MANUFACTURER	Pelikan Hardcopy Production AG Gewerbestrasse 9 CH-8132 Egg/ZH Switzerland +41 (0) 44 986 1111
EMERGENCY TELEPHONE	+41 (0) 44 986 1111 (available only during office hours)		

#### 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CARBON BLACK	215-609-9	1333-86-4	1-5%	-
DYESTUFF	250-774-0	31714-55-3	1-5%	-
IRON OXIDE	215-169-8	1309-38-2	1-5%	-
METAL-ORGANIC COMPLEX	403-360-0	42405-40-3	1-5%	F;R11 Xn;R22 N;R50/53
POLYESTER RESIN		25038-59-9	60-100%	-
POLYPROPYLENE WAX		9003-07-0	1-5%	-

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

This toner does not contain: Substances of Very High Concern (SVHC). The current Candidate List of SVHC for Authorisation can be found (in English only) on the European Chemicals Agency (ECHA) website: [http://echa.europa.eu/chem\\_data/candidate\\_list\\_table\\_en.asp](http://echa.europa.eu/chem_data/candidate_list_table_en.asp).

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

When in doubt or symptoms persist, seek medical attention.

##### INHALATION

General first aid, rest, warmth and fresh air.

##### INGESTION

Immediately rinse mouth and drink plenty of water (200-300 ml).

##### SKIN CONTACT

Wash skin thoroughly with soap and water.

##### EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Fire can be extinguished using: Carbon dioxide (CO<sub>2</sub>). Water spray, fog or mist. Foam.

**27.189: Pelikan toner for Oki B410 / B430 / B440 / B4100 / B4200 / B4300 / B2200 / B2400 / B4400 / B4600****SPECIAL FIRE FIGHTING PROCEDURES**

Avoid breathing fire vapours.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Combustible solid.

**SPECIFIC HAZARDS**

Dust may form an explosive mixture in the atmosphere. Lower explosive limit: ca 15% (in air). By fire, toxic gases may be formed (CO<sub>x</sub>, NO<sub>x</sub>).

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Use protective gloves, goggles and suitable protective clothing. Do not smoke, use naked flames or other sources of ignition.

**SPILL CLEAN UP METHODS**

Avoid generation and spreading of dust. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into closed container. Wash contaminated area with water. For waste disposal, see section 13.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Observe good industrial hygiene practices. Keep away from heat, sparks and open flame. Do not eat, drink or smoke when using the product. Avoid handling which leads to dust formation. Avoid inhalation of dust.

**STORAGE PRECAUTIONS**

Store in closed original container at temperatures between 0°C and 40°C. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION****STD**

General dust recommended limits (UK): 10 mg/m<sup>3</sup> (8-hour TWA) total inhalable dust or 4 mg/m<sup>3</sup> (8-hour TWA) total respirable dust.

**ENGINEERING MEASURES**

Provide adequate ventilation.

**HAND PROTECTION**

Protective gloves are recommended.

**EYE PROTECTION**

Wear dust resistant safety goggles where there is danger of eye contact.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Powder, dust		
COLOUR	Black		
ODOUR	Slight odour		
SOLUBILITY	Insoluble in water		
MELTING POINT (°C)	120	BULK DENSITY	1000-1700 kg/m <sup>3</sup>
VAPOUR PRESSURE	NA	pH-VALUE, DILUTED SOLUTION	NA
AUTO IGNITION TEMPERATURE (°C)	> 360		

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use. Stable at least up to ca 200 °C.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**11 TOXICOLOGICAL INFORMATION****GENERAL INFORMATION**

Mutagenicity, the induction of inheritable genetic damage (Ames Test): negative.

**INHALATION**

Dust may irritate respiratory system or lungs.

**27.189: Pelikan toner for Oki B410 / B430 / B440 / B4100 / B4200 / B4300 / B2200 / B2400 / B4400 / B4600****INGESTION**

No harmful effects expected in amounts likely to be ingested by accident.

**SKIN CONTACT**

Powder may irritate skin.

**EYE CONTACT**

May cause temporary eye irritation.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

The product is not expected to be hazardous to the environment. Volatile organic compounds (VOC): 0%.

**WATER HAZARD CLASSIFICATION**

N/A

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Waste is classified as hazardous waste. Disposal should be in accordance with local, state or national legislation.

**DISPOSAL METHODS**

Recover and reclaim or recycle, if practical. Contact supplier for disposal information. Incineration by an approved method could be considered.

**WASTE CLASS**

List of Wastes (ref: Decision 2000/532/EC): 08 03 17\*. Properties of wastes which render them hazardous (ref: Dir 91/689/EEC Ann III): H14.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**15 REGULATORY INFORMATION****RISK PHRASES**

NC Not classified.

**SAFETY PHRASES**

NC Not classified.

**UK REGULATORY REFERENCES**

Health and Safety at Work Act 1974.

**ENVIRONMENTAL LISTING**

Environmental Protection Act 1990. Pollution Prevention and Control Act 1999.

**EU DIRECTIVES**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**STATUTORY INSTRUMENTS**

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

**APPROVED CODE OF PRACTICE**

Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES**

Classification and Labelling of Substances and Preparations Dangerous for Supply.

**NATIONAL REGULATIONS**

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits EH40. Hazardous Waste Regulations 2005. List of Wastes Regulations 2005. The Solvent Emissions Regulations 2004.

**16 OTHER INFORMATION**

NA = not applicable. NC = not classified. ND = no data. TWA = time-weighted average. Not classified as hazardous for users. All components are pre-registered at the European Chemicals Agency (ECHA). This Safety Data Sheet satisfies the requirements of the REACH Regulation (EC): No 1907/2006, as corrected. Article 31. The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The precise composition of this product is proprietary information. More details will be supplied in confidence to qualified medical personnel if specific treatment is necessary. All brand names and trademarks are the property of their respective holders and are used here for descriptive purposes only.

Changes to Section(s): 13

REVISION DATE D / 09.12.09

SDS NO. 27.189

NC	Not classified.
R11	Highly flammable.
R22	Harmful if swallowed.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.