

IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

DISTRIBUTOR: Pelikan Hardcopy European Logistics & Services GmbH
Neue Strasse 19
D-52382 Niederrhein 2 Germany
Telephone: +49 (0) 2428 830

ADMIN/TECH CENTRE: Pelikan Hardcopy (International) AG
Gewerbestrasse 9
CH-8132 Egg/ZH Switzerland
Telephone: +41 (0) 1 986 1111



Emergency Telephone: +41 (0) 1 986 1111

SAFETY DATA SHEET

PRODUCT: Pelikan inks for: Epson Stylus Color (2292;2301;2314;2321)

2 COMPOSITION / INFORMATION ON INGREDIENTS

	Ingredients	CAS No.	EC No.	Weight %	Symbols	R-Phrases
###	diethylene glycol	111-46-6	203-872-2	5-15	Xn	22
###	1-propoxy-2-propanol	1569-01-3	216-372-4	5-10	---	10

3 HAZARDS IDENTIFICATION

- ###
- No hazard expected under normal conditions of use
 - See Section 16.1 for ingredient R-phrases

4 FIRST-AID MEASURES**CONTACT WITH SKIN**

- Wash affected area with plenty of soap and water

CONTACT WITH EYES

- If substance has got into eyes, immediately wash out with plenty of water

INGESTION

- Give water or milk to drink
- Seek immediate medical attention

INHALATION

- Remove patient to fresh air
- Keep warm and at rest

OTHER INFORMATION

- When in doubt or symptoms persist, seek medical attention

5 FIRE-FIGHTING MEASURES

- Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions
- Toxic and irritant fumes may be formed

6 ACCIDENTAL RELEASE MEASURES

- Shut off all ignition sources
- Absorb spillage in suitable inert material
- Ventilate the area and wash spill site after material pick-up is complete
- See Section 13

7 HANDLING AND STORAGE**7.1 HANDLING**

- The usual precautions for handling chemicals should be observed

7.2 STORAGE

- Keep in a cool, dry, well ventilated place
-

8 EXPOSURE CONTROLS / PERSONAL PROTECTION**8.1 GENERAL**

- Use good personal hygiene practices

8.2 EXPOSURE LIMITS

###

- diethylene glycol

Constituent Exposure Limit:

OES / LTEL 23 ppm 101 mg/m³OES / STEL --- ppm --- mg/m³(Germany) MAK 10 ppm 44 mg/m³

###

- 1-propoxy-2-propanol

No exposure limits have been set for this substance

9 PHYSICAL AND CHEMICAL PROPERTIES

- Liquid, coloured, miscible with water
 - Perceptible odour
 - Non-combustible
 - Boiling point ca 100 deg C
 - Flash point NA deg C (CC)
 - pH 8.3-9.2
 - Density 1.03-1.05 g/cm³ at 25 deg C
 - Vapour pressure 23 mbar
 - Viscosity 2.49-3.01 centipoise
-

10 STABILITY AND REACTIVITY

- Keep away from heat
 - Keep away from strong oxidizing substances
 - Decomposition products may include nitrogen and carbon oxides
-

11 TOXICOLOGICAL INFORMATION

- By comparison with another product:
 - LD50 (oral,rat) > 24 000 mg/kg
 - Vapours or aerosols may cause irritation of eyes, nose and respiratory tract
 - May cause gastrointestinal disturbances
-

12 ECOLOGICAL INFORMATION

- Water Hazard Class 1 (Company)
-

13 DISPOSAL CONSIDERATIONS

- Disposal should be in accordance with local, state or national legislation
-

14 TRANSPORT INFORMATION**14.1 REGULATIONS**

- Proper Shipping Name: NA

14.2 GENERAL

- Not classified as hazardous for transport
-

15 REGULATORY INFORMATION

###

- Not hazardous according to current Dangerous Preparations Directive (1999/45/EC)
 - Not hazardous according to current CHIP Regulations
 - Not hazardous according to current Gefährliche Stoffe Verordnung
 - Not classified as hazardous for users
 - The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents
-

15.1 RISK PHRASES

- None assigned
-

15.2 SAFETY PHRASES

- None assigned
-

16 OTHER INFORMATION

16.1

- R10: Flammable

###

- R22: Harmful if swallowed
-

16.2

- The precise composition of this product is proprietary information. More details will be supplied in confidence to qualified medical personnel if specific treatment is necessary.
 - This product conforms to all known European chemicals safety legislation.
 - Water Hazard Class: 1 = slight, 2 = medium, 3 = severe hazard.
 - NA = not applicable; NC = not classified; ND = no data; TWA = time-weighted average.
 - LTEL = 8hr TWA; STEL = 15min TWA; ppm = parts per million.
 - ### = changes to section since last revision.
 - The above information relates only to the safety of the product designated, based on our current state of knowledge. No responsibility is accepted for any errors or omissions.
-