

**IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY / UNDERTAKING**

DISTRIBUTOR: Pelikan Hardcopy European Logistics & Services GmbH  
Neue Strasse 19  
D-52382 Niederrhein 2 Germany  
Telephone: +49 (0) 2428 830

ADMIN/TECH CENTRE: Pelikan Hardcopy (International) AG  
Gewerbstrasse 9  
CH-8132 Egg/ZH Switzerland  
Telephone: +41 (0) 1 986 1111



Emergency Telephone: +41 (0) 1 986 1111

**SAFETY DATA SHEET**

PRODUCT: Pelikan inks for: Canon BJC800 (1322;1333;1345;1352)

**2 COMPOSITION / INFORMATION ON INGREDIENTS**

	Ingredients	CAS No.	EC No.	Weight %	Symbols	R-Phrases
###	Diethylene glycol (blk/mag)	111-46-6	203-872-2	5-10	Xn	22
###	Propan-2-ol	67-63-0	200-661-7	< 5	F,Xi	11,36,67

**3 HAZARDS IDENTIFICATION**

- ###
- No hazard expected under normal conditions of use
  - See Section 16.1 for ingredient R-Phrases

**4 FIRST-AID MEASURES****CONTACT WITH SKIN**

- Wash affected area with plenty of soap and water

**CONTACT WITH EYES**

- If substance has got into eyes, immediately wash out with plenty of water

**INGESTION**

- Give water or milk to drink
- Seek immediate medical attention

**INHALATION**

- Remove patient to fresh air
- Keep warm and at rest

**OTHER INFORMATION**

- When in doubt or symptoms persist, seek medical attention

**5 FIRE-FIGHTING MEASURES**

- Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions
- Toxic and irritant fumes may be formed

**6 ACCIDENTAL RELEASE MEASURES**

- Shut off all ignition sources
- Absorb spillage in suitable inert material
- Ventilate the area and wash spill site after material pick-up is complete
- See Section 13

---

**7 HANDLING AND STORAGE****7.1 HANDLING**

- The usual precautions for handling chemicals should be observed

**7.2 STORAGE**

- Keep in a cool, dry, well ventilated place
- 

**8 EXPOSURE CONTROLS AND PERSONAL PROTECTION****8.1 GENERAL**

- Use good personal hygiene practices

**8.2 EXPOSURE LIMITS**

###

- Diethylene glycol (blk/mag)

Constituent Exposure Limit:

OES / LTEL 23 ppm 101 mg/m3

OES / STEL --- ppm --- mg/m3

(Germany) MAK 10 ppm 44 mg/m3

###

- Propan-2-ol

OES / LTEL 400 ppm 999 mg/m3

OES / STEL 500 ppm 1250 mg/m3

(Germany) MAK 200 ppm 500 mg/m3

**9 PHYSICAL AND CHEMICAL PROPERTIES**

- Liquid, coloured, aqueous solution
  - Perceptible odour
  - Non-combustible
  - Boiling point ca 100 deg C
  - Flash point NA deg C (CC)
  - pH 7.4
  - Density 1.02-1.04 g/cm3 at 25 deg C
  - Vapour pressure 23 mbar
- 

**10 STABILITY AND REACTIVITY**

- Keep away from heat
  - Keep away from strong oxidizing substances
  - Decomposition products may include nitrogen and carbon oxides
- 

**11 TOXICOLOGICAL INFORMATION**

- Vapours or aerosols may cause irritation of eyes, nose and respiratory tract
  - Can be absorbed through skin
  - May cause gastrointestinal disturbances
- 

**12 ECOLOGICAL INFORMATION**

###

- Water Hazard Class 1-2 (Company)
- 

**13 DISPOSAL CONSIDERATIONS**

- Disposal should be in accordance with local, state or national legislation
- 

**14 TRANSPORT INFORMATION****14.1 REGULATIONS**

- Proper Shipping Name: NA

**14.2 GENERAL**

- Not classified as hazardous for transport
-

---

**15 REGULATORY INFORMATION**

###

- Not hazardous according to current Dangerous Preparations Directive (1999/45/EC)
- Not hazardous according to current CHIP Regulations
- Not hazardous according to current Gefährliche Stoffe Verordnung
- Not classified as hazardous for users
- The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents

---

**15.1 RISK PHRASES**

- None assigned

---

**15.2 SAFETY PHRASES**

- None assigned
- 

**16 OTHER INFORMATION****16.1 INGREDIENT R-PHRASES**

###

- R11: Highly Flammable
- R22: Harmful if swallowed
- R36: Irritating to eyes
- R67: Vapours may cause drowsiness and dizziness

- 
- 16.2
- The precise composition of this product is proprietary information. More details will be supplied in confidence to qualified medical personnel if specific treatment is necessary.
  - This product conforms to all known European chemicals safety legislation.
  - Water Hazard Class: 1 = slight, 2 = medium, 3 = severe hazard.
  - NA = not applicable; NC = not classified; ND = no data; TWA = time-weighted average.
  - LTEL = 8hr TWA; STEL = 15min TWA; ppm = parts per million.
  - ### = changes to section since last revision.
  - The above information relates only to the safety of the product designated, based on our current state of knowledge. No responsibility is accepted for any errors or omissions.
-