

IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY / UNDERTAKING

DISTRIBUTOR: Pelikan Hardcopy European Logistics & Services GmbH
Neue Strasse 19
D-52382 Niederzier 2 Germany
Telephone: +49 (0) 2428 830

ADMIN/TECH CENTRE: Pelikan Hardcopy (International) AG
Gewerbestrasse 9
CH-8132 Egg/ZH Switzerland
Telephone: +41 (0) 1 986 1111



Emergency Telephone: +41 (0) 1 986 1111

SAFETY DATA SHEET

PRODUCT: Pelikan inks for: HP Deskjet 500/550C (1395;1403;1413)

2 COMPOSITION / INFORMATION ON INGREDIENTS

	Ingredients	CAS No.	EC No.	Weight %	Symbols	R-Phrases
###	Diethylene glycol	111-46-6	203-872-2	5-15	Xn	22
###	Ethoxylated tetramethyldacynediol	9014-85-1	-	< 5	Xi	36

3 HAZARDS IDENTIFICATION

- ###
- No hazard expected under normal conditions of use
 - See Section 16.1 for ingredient R-Phrases

4 FIRST-AID MEASURES**CONTACT WITH SKIN**

- Wash affected area with plenty of soap and water

CONTACT WITH EYES

- If substance has got into eyes, immediately wash out with plenty of water

INGESTION

- Give water or milk to drink
- Seek immediate medical attention

INHALATION

- Remove patient to fresh air
- Keep warm and at rest

OTHER INFORMATION

- When in doubt or symptoms persist, seek medical attention

5 FIRE-FIGHTING MEASURES

- Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions
- Toxic and irritant fumes may be formed

6 ACCIDENTAL RELEASE MEASURES

- Shut off all ignition sources
- Absorb spillage in suitable inert material
- Ventilate the area and wash spill site after material pick-up is complete
- See Section 13

7 HANDLING AND STORAGE**7.1 HANDLING**

- The usual precautions for handling chemicals should be observed

7.2 STORAGE

- Keep in a cool, dry, well ventilated place
-

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**8.1 GENERAL**

###

- Wear plastic gloves
- Use good personal hygiene practices

8.2 EXPOSURE LIMITS

###

- Diethylene glycol

Constituent Exposure Limit:

OES / LTEL 23 ppm 101 mg/m³OES / STEL --- ppm --- mg/m³(Germany) MAK 10 ppm 44 mg/m³

###

- Ethoxylated tetramethyldacynediol

No exposure limits have been set for this substance

9 PHYSICAL AND CHEMICAL PROPERTIES

- Liquid, coloured, aqueous solution, miscible with water
 - Sweet ether-like odour
 - Non-combustible
 - Boiling point ca 100 deg C
 - Flash point NA deg C (CC)
 - pH ca 8
 - Density 1.03-1.04 g/cm³ at 25 deg C
 - Vapour pressure ca 23 mbar
-

10 STABILITY AND REACTIVITY

- Keep away from heat
 - Keep away from strong oxidizing substances
 - Decomposition products may include nitrogen and carbon oxides
-

11 TOXICOLOGICAL INFORMATION

- Vapours or aerosols may cause irritation of eyes, nose and respiratory tract
 - Can be absorbed through skin
 - May cause gastrointestinal disturbances
-

12 ECOLOGICAL INFORMATION

- Water Hazard Class 1 (Company)
-

13 DISPOSAL CONSIDERATIONS

- Disposal should be in accordance with local, state or national legislation
-

14 TRANSPORT INFORMATION**14.1 REGULATIONS**

- Proper Shipping Name: NA

14.2 GENERAL

- Not classified as hazardous for transport
-

15 REGULATORY INFORMATION

###

- Not hazardous according to current Dangerous Preparations Directive (1999/45/EC)
- Not hazardous according to current CHIP Regulations
- Not hazardous according to current Gefährliche Stoffe Verordnung
- Not classified as hazardous for users
- The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents

15.1 RISK PHRASES

- None assigned

15.2 SAFETY PHRASES

- None assigned
-

16 OTHER INFORMATION**16.1 INGREDIENT R-PHRASES**

###

- R22: Harmful if swallowed
- R36: Irritating to eyes

16.2

- The precise composition of this product is proprietary information. More details will be supplied in confidence to qualified medical personnel if specific treatment is necessary.
 - This product conforms to all known European chemicals safety legislation.
 - Water Hazard Class: 1 = slight, 2 = medium, 3 = severe hazard.
 - NA = not applicable; NC = not classified; ND = no data; TWA = time-weighted average.
 - LTEL = 8hr TWA; STEL = 15min TWA; ppm = parts per million.
 - ### = changes to section since last revision.
 - The above information relates only to the safety of the product designated, based on our current state of knowledge. No responsibility is accepted for any errors or omissions.
-