



SAFETY DATA SHEET
22.999: Pelikan black ink (pigment / oil-based) for Tally

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME 22.999: Pelikan black ink (pigment / oil-based) for Tally

SUPPLIER Pelikan Hardcopy European
Logistics & Services GmbH
Neue Strasse 19
D-52382 Niederzier 2
Germany
+49 (0) 2428 830
Olaf Lehmann
olaf.lehmann@phpag.com

EMERGENCY TELEPHONE +41 (0) 44 986 1111 (available only during office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE; GASOIL - UNSPECIFIED	265-148-2	64742-46-7	60-100%	Xn;R65. R66.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Remove victim immediately from source of exposure. General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

INHALATION

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Immediately remove contaminated clothing. Wash the skin immediately with soap and water.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Combustible. Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid water in straight hose stream; will scatter and spread fire. Containers close to fire should be removed immediately or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Vapours are heavier than air and may spread near ground to sources of ignition. May ignite at high temperature.

SPECIFIC HAZARDS

By fire, toxic gases may be formed (COx, NOx).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

22.999: Pelikan black ink (pigment / oil-based) for Tally**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Keep combustibles away from spilled material. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Protect from freezing and direct sunlight. Store separated from: Acids. Oxidising material.

STORAGE CLASS

Miscellaneous hazardous material storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE; GASOIL - UNSPECIFIED	WEL		5 mg/m ³		10 mg/m ³	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT**ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

Wear full face mask supplied with: Gas cartridge suitable for organic substances.

HAND PROTECTION

Use protective gloves made of: Multi-layer material (e.g. 4H, Saranex). PVC gloves are recommended. Nitrile. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved safety goggles.

OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Black		
ODOUR	Oil smell		
SOLUBILITY	Soluble in Organic solvents. Not soluble in water.		
BOILING POINT (°C)	200-300 @ 760 mm Hg	RELATIVE DENSITY	0.8 - 1.1 @ 25 °C
VAPOUR DENSITY (air=1)	> 1	VAPOUR PRESSURE	< 1 mm Hg @ 25 °C

22.999: Pelikan black ink (pigment / oil-based) for Tally

pH-VALUE, CONC. SOLUTION	NA	VISCOSITY	> 7 cSt @ 25 °C
FLASH POINT (°C)	120 CC (Closed cup).	PARTITION COEFFICIENT (N-Octanol/Water)	ND
SOLUBILITY VALUE (g/100g H2O@20°C)	< 10		

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

HAZARDOUS POLYMERISATION

Not relevant.

MATERIALS TO AVOID

Strong oxidising substances. Strong acids. Strong alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

11 TOXICOLOGICAL INFORMATION**INHALATION**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Anaesthetic in high concentrations. Central nervous system depression.

INGESTION

Harmful: may cause lung damage if swallowed. Gastrointestinal symptoms, including upset stomach.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritating and may cause redness and pain.

HEALTH WARNINGS

Ingredient Distillates (Petroleum) (CAS: 64742-46-7) is not carcinogenic as manufactured from a non-carcinogenic raw material. (Nota N).

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Volatile organic compounds (VOC): 0%.

MOBILITY

The product is immiscible with water and will spread on the water surface. Large volumes may penetrate soil and contaminate groundwater.

BIOACCUMULATION

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

DEGRADABILITY

The product is degraded completely by photochemical oxidation.

ACUTE FISH TOXICITY

The product is not expected to be toxic to aquatic organisms.

WATER HAZARD CLASSIFICATION

WGK 3 (Severe hazard)(Self-classification).

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Disposal should be in accordance with local, state or national legislation.

DISPOSAL METHODS

Recover and reclaim or recycle, if practical. Do not allow runoff to sewer, waterway or ground. Incinerate in suitable combustion chamber. Dispose of waste and residues in accordance with local authority requirements.

WASTE CLASS

List of Wastes (ref: Decision 2000/532/EC): 08 03 12*. Properties of wastes which render them hazardous (ref: Dir 91/689/EEC Ann III): H5.

22.999: Pelikan black ink (pigment / oil-based) for Tally**14 TRANSPORT INFORMATION**

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

P13 Safety data sheet available for professional user on request.

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974. Petroleum (Consolidation) Act, as amended 1984 SI 1244.

ENVIRONMENTAL LISTING

Environmental Protection Act 1990. Pollution Prevention and Control Act 1999.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits EH40. Hazardous Waste Regulations 2005. List of Wastes Regulations 2005. The Solvent Emissions Regulations 2004. US Toxic Substances Control Act (TSCA) & Canadian Domestic Substances List (DSL) status: All ingredients of this material are listed.

16 OTHER INFORMATION

GENERAL INFORMATION

NA = not applicable. NC = not classified. ND = no data. TWA = time-weighted average. This Safety Data Sheet satisfies the requirements of the REACH Regulation (EC): No 1907/2006, as corrected. Article 31. All brand names and trademarks are the property of their respective holders and are used here for descriptive purposes only.

REVISION COMMENTS

Changes to Section(s): 15 16

REVISION DATE I / 18.01.10

SDS NO. 22.999

RISK PHRASES IN FULL

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.