



**SAFETY DATA SHEET**  
**22.995: Pelikan green ink analogue (oil-based) for Tally**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING**

PRODUCT NAME 22.995: Pelikan green ink analogue (oil-based) for Tally

SUPPLIER Pelikan Hardcopy European  
Logistics & Services GmbH  
Neue Strasse 19  
D-52382 Niederrhein 2  
Germany  
+49 (0) 2428 830  
Olaf Lehmann  
olaf.lehmann@phpag.com

EMERGENCY TELEPHONE +41 (0) 44 986 1111 (available only during office hours)

**2 HAZARDS IDENTIFICATION**

Repeated exposure may cause skin dryness or cracking. Harmful: may cause lung damage if swallowed.

**3 COMPOSITION/INFORMATION ON INGREDIENTS**

Name	EC No.	CAS-No.	Content	Classification
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE; GASOIL - UNSPECIFIED	265-148-2	64742-46-7	60-100%	Xn;R65. R66.

The Full Text for all R-Phrases are Displayed in Section 16

**4 FIRST-AID MEASURES**

**GENERAL INFORMATION**

Remove victim immediately from source of exposure. If breathing stops, provide artificial respiration. Get medical attention immediately!

**INHALATION**

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention immediately.

**INGESTION**

Remove victim immediately from source of exposure. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Danger of aspiration and development of chemical pneumonia. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Get medical attention immediately!

**SKIN CONTACT**

Remove victim immediately from source of exposure. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Get medical attention promptly if symptoms occur after washing.

**EYE CONTACT**

Remove victim immediately from source of exposure. Promptly wash eyes with plenty of water while lifting the eye lids. Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

**5 FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA**

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc. DO NOT use water if avoidable.

**SPECIAL FIRE FIGHTING PROCEDURES**

Avoid water in straight hose stream; will scatter and spread fire. Containers close to fire should be removed immediately or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Vapours are heavier than air and may spread near ground to sources of ignition.

**SPECIFIC HAZARDS**

By fire, toxic gases may be formed (COx, NOx).

**PROTECTIVE MEASURES IN FIRE**

Wear full protective clothing.

**22.995: Pelikan green ink analogue (oil-based) for Tally****6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area. Avoid inhalation of vapours. Avoid contact with skin and eyes.

**ENVIRONMENTAL PRECAUTIONS**

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

**SPILL CLEAN UP METHODS**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Keep combustibles away from spilled material. Stop leak if possible without risk. Do not contaminate water sources or sewer. Absorb in vermiculite, dry sand or earth and place into containers.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Storage tanks and other containers must be grounded. Static electricity and formation of sparks must be prevented. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Avoid spilling, skin and eye contact. Handle and open container with care. Risk of excess pressure build-up.

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place. Protect from light, including direct sunrays. Ground container and transfer equipment to eliminate static electric sparks. Avoid contact with oxidising agents.

**STORAGE CLASS**

Flammable liquid storage.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE; GASOIL - UNSPECIFIED	WEL		5 mg/m <sup>3</sup>		10 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT****ENGINEERING MEASURES**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

**RESPIRATORY EQUIPMENT**

Wear full face mask supplied with: Gas cartridge suitable for organic substances.

**HAND PROTECTION**

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile. Viton rubber (fluor rubber). Be aware that the liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Wear approved safety goggles.

**OTHER PROTECTION**

Wear suitable protective clothing as protection against splashing or contamination.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid		
COLOUR	Green		
ODOUR	Characteristic Hydrocarbon		
SOLUBILITY	Soluble in Organic solvents. Not soluble in water.		
BOILING POINT (°C)	200-300 @ 760 mm Hg	RELATIVE DENSITY	0.85-0.99 @ 25 °C

**22.995: Pelikan green ink analogue (oil-based) for Tally**

VAPOUR DENSITY (air=1)	> 1	pH-VALUE, CONC. SOLUTION	NA
VISCOSITY	6-15 cps @ 25 °C	FLASH POINT (°C)	120 CC (Closed cup).
AUTO IGNITION	200	PARTITION COEFFICIENT	ND
TEMPERATURE (°C)		(N-Octanol/Water)	
SOLUBILITY VALUE (g/100g H <sub>2</sub> O@20°C)	< 10		

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions and recommended use.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents.

**HAZARDOUS POLYMERISATION**

Not relevant.

**MATERIALS TO AVOID**

No incompatible groups noted.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Nitrous gases (NO<sub>x</sub>).

**11 TOXICOLOGICAL INFORMATION****INHALATION**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Anaesthetic in high concentrations. Central nervous system depression.

**INGESTION**

Harmful: may cause lung damage if swallowed.

**SKIN CONTACT**

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

**EYE CONTACT**

Vapour or spray may cause temporary (reversible) eye damage.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Volatile organic compounds (VOC): 0%.

**MOBILITY**

The product is immiscible with water and will spread on the water surface. Large volumes may penetrate soil and contaminate groundwater.

**DEGRADABILITY**

The product is degraded completely by photochemical oxidation.

**ACUTE FISH TOXICITY**

The product is not expected to be toxic to aquatic organisms.

**WATER HAZARD CLASSIFICATION**

WGK 3 (Severe hazard)(Self-classification).

**13 DISPOSAL CONSIDERATIONS****GENERAL INFORMATION**

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority. Disposal should be in accordance with local, state or national legislation.

**DISPOSAL METHODS**

Recover and reclaim or recycle, if practical. Do not allow runoff to sewer, waterway or ground. Incinerate in suitable combustion chamber. Dispose of waste and residues in accordance with local authority requirements.

**WASTE CLASS**

List of Wastes (ref: Decision 2000/532/EC): 08 03 12\*. Properties of wastes which render them hazardous (ref: Dir 91/689/EEC Ann III): H5.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

**22.995: Pelikan green ink analogue (oil-based) for Tally****15 REGULATORY INFORMATION**

## LABELLING



Harmful

## CONTAINS

DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE; GASOIL - UNSPECIFIED

## RISK PHRASES

R66 Repeated exposure may cause skin dryness or cracking.

R65 Harmful: may cause lung damage if swallowed.

## SAFETY PHRASES

S37 Wear suitable gloves.

S60 This material and its container must be disposed of as hazardous waste.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## UK REGULATORY REFERENCES

Health and Safety at Work Act 1974. Petroleum (Consolidation) Act, as amended 1984 SI 1244.

## ENVIRONMENTAL LISTING

Environmental Protection Act 1990. Pollution Prevention and Control Act 1999.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

## APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations.

## GUIDANCE NOTES

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits EH40. Hazardous Waste Regulations 2005. List of Wastes Regulations 2005. The Solvent Emissions Regulations 2004.

**16 OTHER INFORMATION**

## GENERAL INFORMATION

NA = not applicable. NC = not classified. ND = no data. TWA = time-weighted average. This Safety Data Sheet satisfies the requirements of the REACH Regulation (EC): No 1907/2006, as corrected. Article 31. All brand names and trademarks are the property of their respective holders and are used here for descriptive purposes only.

## REVISION COMMENTS

Changes to Section(s): 15 16

REVISION DATE F / 18.01.10

SDS NO. 22.995

## RISK PHRASES IN FULL

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.