



SAFETY DATA SHEET

27.961: Pelikan cyan / magenta / yellow toners for Lexmark C522 / 524

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	27.961: Pelikan cyan / magenta / yellow toners for Lexmark C522 / 524
SUPPLIER	Pelikan Hardcopy European Logistics & Services GmbH Neue Strasse 19 D-52382 Niederzier 2 Germany +49 (0) 2428 830 Olaf Lehmann olaf.lehmann@phpag.com
EMERGENCY TELEPHONE	+41 (0) 44 986 1111 (available only during office hours)

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

HUMAN HEALTH

Dust may irritate respiratory system or lungs. May irritate eyes.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
AMORPHOUS SILICON DIOXIDE (chemically produced)	231-545-4	7631-86-9	1-5%	-
BLUE PIGMENT (cyan toner only)	205-685-1	147-14-8	1-5%	-
METAL-ORGANIC COMPLEX	403-360-0	42405-40-3	1-5%	F;R11 Xn;R22 N;R50/53
POLYESTER RESIN (confidential CAS Number)			60-100%	-
RED PIGMENT (confidential CAS Number / magenta toner only)			1-5%	-
WAX (confidential CAS Number)			1-5%	-
YELLOW PIGMENT (yellow toner only)	224-867-1	4531-49-1	1-5%	-

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

When in doubt or symptoms persist, seek medical attention.

INHALATION

General first aid, rest, warmth and fresh air.

INGESTION

Immediately rinse mouth and drink plenty of water (200-300 ml).

SKIN CONTACT

Wash skin thoroughly with soap and water.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Carbon dioxide (CO₂). Water spray, fog or mist. Foam. Dry chemicals.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

27.961: Pelikan cyan / magenta / yellow toners for Lexmark C522 / 524

SPECIFIC HAZARDS

Dust may form an explosive mixture in the atmosphere. In case of fire, toxic gases may be formed.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Use protective gloves, goggles and suitable protective clothing. Do not smoke, use naked flames or other sources of ignition.

SPILL CLEAN UP METHODS

Avoid generation and spreading of dust. Collect powder using special dust vacuum cleaner with particle filter or carefully sweep into closed container. Wash contaminated area with water. For waste disposal, see section 13.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Observe good industrial hygiene practices. Keep away from heat, sparks and open flame. Do not eat, drink or smoke when using the product. Avoid handling which leads to dust formation. Avoid inhalation of dust.

STORAGE PRECAUTIONS

Store in closed original container at temperatures between 0°C and 40°C. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

STD

General dust recommended limits (UK): 10 mg/m³ (8-hour TWA) total inhalable dust or 4 mg/m³ (8-hour TWA) total respirable dust.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

HAND PROTECTION

Protective gloves are recommended.

EYE PROTECTION

Wear dust resistant safety goggles where there is danger of eye contact.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Powder, dust		
COLOUR	Blue Red Yellow		
ODOUR	Slight odour		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	NA	MELTING POINT (°C)	100 - 140
RELATIVE DENSITY	> 1.0	BULK DENSITY	ND
VAPOUR PRESSURE	NA	pH-VALUE, DILUTED SOLUTION	NA
FLASH POINT (°C)	NA	AUTO IGNITION	NA
		TEMPERATURE (°C)	
PARTITION COEFFICIENT (N-Octanol/Water)	NA		

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

HAZARDOUS POLYMERISATION

Will not polymerise.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Mutagenicity, the induction of inheritable genetic damage (Ames Test): negative.

27.961: Pelikan cyan / magenta / yellow toners for Lexmark C522 / 524**INHALATION**

Dust may irritate respiratory system or lungs.

INGESTION

No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Powder may irritate skin.

EYE CONTACT

May cause temporary eye irritation.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product is not expected to be hazardous to the environment. Volatile organic compounds (VOC): 0%.

BIOACCUMULATION

No data available on bioaccumulation.

DEGRADABILITY

The product is not expected to be biodegradable.

WATER HAZARD CLASSIFICATION

N/A

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

Waste is classified as hazardous waste. Disposal should be in accordance with local, state or national legislation.

DISPOSAL METHODS

Recover and reclaim or recycle, if practical. Contact supplier for disposal information. Incineration by an approved method could be considered.

WASTE CLASS

List of Wastes (ref: Decision 2000/532/EC): 08 03 17*. Properties of wastes which render them hazardous (ref: Dir 91/689/EEC Ann III): H14.

14 TRANSPORT INFORMATION**GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

15 REGULATORY INFORMATION**RISK PHRASES**

NC Not classified.

SAFETY PHRASES

NC Not classified.

UK REGULATORY REFERENCES

Health and Safety at Work Act 1974.

ENVIRONMENTAL LISTING

Environmental Protection Act 1990. Pollution Prevention and Control Act 1999.

EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations.

27.961: Pelikan cyan / magenta / yellow toners for Lexmark C522 / 524

GUIDANCE NOTES

Classification and Labelling of Substances and Preparations Dangerous for Supply.

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits EH40. Hazardous Waste Regulations 2005. List of Wastes Regulations 2005. The Solvent Emissions Regulations 2004.

16 OTHER INFORMATION

GENERAL INFORMATION

NA = not applicable. NC = not classified. ND = no data. TWA = time-weighted average. Not classified as hazardous for users. This Safety Data Sheet satisfies the requirements of the REACH Regulation (EC): No 1907/2006, as corrected. Article 31. All brand names and trademarks are the property of their respective holders and are used here for descriptive purposes only.

REVISION COMMENTS

Changes to Section(s): 13

REVISION DATE B / 11.12.09

SDS NO. 27.961

RISK PHRASES IN FULL

NC Not classified.

R11 Highly flammable.

R22 Harmful if swallowed.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.