

IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY / UNDERTAKING

DISTRIBUTOR: Pelikan Hardcopy European Logistics & Services GmbH
Neue Strasse 19
D-52382 Niederrhein 2 Germany
Telephone: +49 (0) 2428 830

ADMIN/TECH CENTRE: Pelikan Hardcopy (International) AG
Gewerbstrasse 9
CH-8132 Egg/ZH Switzerland
Telephone: +41 (0) 1 986 1111



Emergency Telephone: +41 (0) 1 986 1111

SAFETY DATA SHEET

PRODUCT: Pelikan ink for: Kleindienste Datentechnik (2111)

2 COMPOSITION / INFORMATION ON INGREDIENTS

	Ingredients	CAS No.	EC No.	Weight %	Symbols	R-Phrases
###	Diethylene glycol	111-46-6	203-872-2	5-10	Xn	22
###	2-(2-butoxyethoxy)ethanol	112-34-5	203-961-6	5-10	Xi	36
###	Triethanolamine	102-71-6	203-049-8	< 5	Xi	36/37/38

3 HAZARDS IDENTIFICATION

- ###
- No hazard expected under normal conditions of use
 - See Section 16.1 for ingredient R-Phrases

4 FIRST-AID MEASURES**CONTACT WITH SKIN**

- Wash affected area with plenty of soap and water

CONTACT WITH EYES

- If substance has got into eyes, immediately wash out with plenty of water

INGESTION

- Give water or milk to drink

INHALATION

- ###
- Remove patient to fresh air
 - Keep warm and at rest

OTHER INFORMATION

- When in doubt or symptoms persist, seek medical attention

5 FIRE-FIGHTING MEASURES

- Not flammable. In case of fire use extinguishing media appropriate to surrounding conditions
- Toxic and irritant fumes may be formed

6 ACCIDENTAL RELEASE MEASURES

- Shut off all ignition sources
- Absorb spillage in suitable inert material
- Ventilate the area and wash spill site after material pick-up is complete
- See Section 13

7 HANDLING AND STORAGE**7.1 HANDLING**

- The usual precautions for handling chemicals should be observed

7.2 STORAGE

- Keep in a cool, dry, well ventilated place
-

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**8.1 GENERAL**

###

- Wear plastic gloves
 - Use good personal hygiene practices
-

8.2 EXPOSURE LIMITS

###

- Diethylene glycol

Constituent Exposure Limit:

OES / LTEL 23 ppm 101 mg/m³OES / STEL --- ppm --- mg/m³(Germany) MAK 10 ppm 44 mg/m³

###

- 2-(2-butoxyethoxy)ethanol

OES / LTEL --- ppm --- mg/m³OES / STEL --- ppm --- mg/m³(Germany) MAK --- ppm 100 mg/m³

###

- Triethanolamine

No exposure limits have been set for this substance

9 PHYSICAL AND CHEMICAL PROPERTIES

- Liquid, black, miscible with water
 - Perceptible odour
 - Non-combustible
 - Boiling point ND deg C
 - Flash point NA deg C (CC)
 - Melting point ND deg C
 - Auto-ignition point ND deg C
 - pH 8.29
 - Density 1.025 g/cm³ at 25 deg C
 - Vapour pressure ca 23 mbar
 - Fat solubility ND kg/l
 - Partition coefficient : n-Octanol/water ND
 - Viscosity 1.19 centipoise at 25 deg C
-

10 STABILITY AND REACTIVITY

- Keep away from heat
 - Keep away from strong oxidizing substances
 - Decomposition products may include nitrogen and carbon oxides
-

11 TOXICOLOGICAL INFORMATION

- By comparison with another product:
 - LD50 (oral,rat) > 100 000 mg/kg
 - Vapours or aerosols may cause irritation of eyes, nose and respiratory tract
 - May cause gastrointestinal disturbances
-

12 ECOLOGICAL INFORMATION

- Water Hazard Class 1 (Company)
-

13 DISPOSAL CONSIDERATIONS

- Disposal should be in accordance with local, state or national legislation
-

14 TRANSPORT INFORMATION**14.1 REGULATIONS**

- Proper Shipping Name: NA
-

14.2 GENERAL

- Not classified as hazardous for transport
-

15 REGULATORY INFORMATION

###

- Not hazardous according to current Dangerous Preparations Directive (1999/45/EC)
 - Not hazardous according to current CHIP Regulations
 - Not hazardous according to current Gefährliche Stoffe Verordnung
 - Not classified as hazardous for users
 - The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents
-

15.1 RISK PHRASES

- None assigned
-

15.2 SAFETY PHRASES

- None assigned
-

16 OTHER INFORMATION**16.1 INGREDIENT R-PHRASES**

###

- R22: Harmful if swallowed
 - R36: Irritating to eyes
 - R36/37/38: Irritating to eyes, respiratory system and skin
-

- 16.2
- The precise composition of this product is proprietary information. More details will be supplied in confidence to qualified medical personnel if specific treatment is necessary.
 - This product conforms to all known European chemicals safety legislation.
 - Water Hazard Class: 1 = slight, 2 = medium, 3 = severe hazard.
 - NA = not applicable; NC = not classified; ND = no data; TWA = time-weighted average.
 - LTEL = 8hr TWA; STEL = 15min TWA; ppm = parts per million.
 - ### = changes to section since last revision.
 - The above information relates only to the safety of the product designated, based on our current state of knowledge. No responsibility is accepted for any errors or omissions.
-